HPCC Year One Progress Report

"A Distributed, Real-time Hurricane Wind Analysis System"

Hurricane Research Division NOAA/AOML, Miami, FL

The following is a progress report for the first year of a three year project entitled "A Distributed, Real-time Hurricane Wind Analysis System". The first year of this project has been funded by NOAA's High Performance Computing and Communications Program, with Matching funds provided through the FEMA-NIBS HAZUS Project.

Updated* Milestones and Deliverables

1.06-01-98

Completion of rapid prototype application for dynamically querying the HURDAT hurricane storm database and delivering query results and storm track plots to the web.

2. 06-15-98

Complete operational build of the 1998 HRD Wind Analysis System.

3. 07-01-98

Complete updates to scripts to download and process observations in real time.

4. 09-01-98

Complete feasibility testing of distributed object technology. Complete testing of IDL for automatic product generation.

5. **10-01-98**

Report on first year project progress.

6. 07-01-98

Completion of Object-Relational Database evaluation

* The project commenced when the HPCC funds were recieved in February 1998.

Progress Report

1. Completion of rapid prototype application for dynamically querying the HURDAT hurricane storm database and delivering query results and storm track plots to the web.

Documentation:

We have developed a rapid prototype application demonstrating dynamic and platform independent delivery of information from an Oracle 8 database with object extensions to the World Wide Web using the JAVA language. Both the database and the web components of the prototype application are hosted

by HRD workstations situated outside of AOML's firewall

(http://www.storm.aoml.noaa.gov/Storms/index.html). The client applet allows for dynamically querying the HURDAT ("Best Track") hurricane storm database and delivering query results and storm track plots to the web and should be accessible from most JAVA 1.1.x capable PC or workstation platforms with internet access.

We have recently announced the public availability of this application on the *Tropical Cyclones* mailing list.

Unfortunately some sites may be temporarily unable to connect for a number of reasons. If a client is running from inside of a firewall, the applet may not be able to access the AOML database without an Oracle SQL*Net proxy in place on their firewall. Also, in some instances, the browser may not be running a version of the Java Runtime Environment (JRE) required to run the applet correctly. For these instances, we have installed a Java Plugin on the web server for updating client browsers to a compatible JRE. The plugin is freely available from JavaSoft and currently only works on Windows95/NT and Solaris based Netscape 3, Netscape 4 and Internet Explorer 4 browsers. Other platforms will follow. In addition to the suggestions made above, users connecting to our applets are also encouraged to download the latest version of a Java enabled browser for up to date JRE and plugin compliance and have at least 32 megabytes of RAM on their machines. The applet performs correctly when it is run outside of the browser using the appletviewer application from a user installed 1.1.x JRE. In addition to possibly encountering problems while attempting to run the applet, users may encounter database login failures because of the limited number of licenses we have purchased (5). While we have attempted to remedy this problem by connecting and disconnecting to and from the database for each query performed, certain queries (such as loading geography) may take an inordinate amount of time and will tie up the number of available licenses.

We completed this milestone ahead of the projected June 1st deadline.

2. Complete operational builds of the workstation-based QC Client and distributed analysis system software for use during the 1998 hurricane season. Scientists at HRD will use the operational builds to provide realtime products to NHC while development efforts move forward throughout the year.

Documentation:

The operational build of the HRD Wind Analysis System is in place and ready for use during the 1998 Atlantic hurricane season. AOML scientists are using this build to deliver near realtime products to NHC.

Development for both the QCClient and Analysis Automation subsystems of the new system is ongoing and progressing steadily. In general, all code is up to date with latest jdk release (1.1.6) and implementation of most basic functionality is complete with the notable exceptions being in the area of database integration.

Most of the client application subproject and analysis subproject functionality requirements have been met. Some of the requirements for the QCClient application include: 1) map loading and drawing, 2) plotting of wind observations and storm track fixes in both synoptic and storm relative coordinates, 3) graphical tools such as zooming, observation flagging (quality control), distance/heading calculation and detailed observation inspection and editing, 4) separate "views" panel for immediate graphical response to any changes to data, and 5) file import and export capabilities for legacy data files and landmarks. Some Analysis subsystem completed requirements include: 1) porting of legacy Fortran code to Solaris and HPUX platforms from VMS Fortran, 2) integration of the Java, C and Fortran code to run analyses on both the Solaris and HPUX platforms and 3) initializing a mock Analysis sequence from the QCClient application.

We have developed a generic set of Java packages (groups of compiled classes) to promote code reuse among all Java implementations by our development team. Code reuse is important for testing, minimizing errors, saving space and saving time. The current upper level packages include "hrd.geography" (classes representing geographical objects such as global positions, global areas, maps, etc...), "hrd.meteorology" (classes representing meteorological objects such as wind observations, storm track fixes, storm tracks, etc...), "hrd.math" (classes representing mathematical objects such as vectors, matrices and angles), "hrd.apps" (classes and subpackages pertaining to applications and the various subsystems of the project), "hrd.db" (classes and interfaces pertaining to general database connectivity), and the utility packages "hrd.util" (non-graphical utilities) and "hrd.awt.util" (abstract-windowing-toolkit [graphical] utilities).

The documentation of a Java development effort is made easier through self documenting source code. The javadoc program available in the JDK creates HTML API references based on developer source code comments with one command. A current API reference, class hierarchy and index of methods and attributes is available to developers at all times.

We completed this milestone ahead of the projected June 15th deadline.

3. Update scripts for downloading and decoding real-time wind observations into the HRD wind analysis system from remote locations at NHC, NCEP, and other sites. Update and enhance processing algorithms to ensure that all input data conform to a common framework for height, averaging time, and exposure. Add new aircraft- and space-based remote sensing wind observing platforms as they become available.

Documentation:

We have completed work on decoders for land-based METAR data, and sea based C-MAN, Bouy, and Ships data that we will be receiving from NHC's family of services feed. These decoders are written in standard ANSI C for portability and performance reasons. In addition to decoders, we have also ported various proven legacy boundary layer conversion routines from FORTRAN to C. These routines and decoders deliver data in formats appropriate for ingestion by our database and by HRD's legacy file-based analysis system.

We are using the Local Data Manager (LDM) software package available from Unidata for most of our realtime data needs. An HRD HPUX server at NHC running LDM listens in on the Hurricane Center's Family Of Services (FOS) data feed from NCEP. These data are stored, decoded, adjusted and sent to the AOML database and legacy filesystem database via HRD's dedicated T1 line to NHC. The data are also fed to several HRD machines at NHC.

The completion date for this task has been pushed back to September 1st because of setbacks experienced in installing, configuring and integrating the LDM software. Most of the framework is complete for this task, but certain adjustment routines have yet to be integrated. As of August 1st, the following data are available to the system via LDM and our decoders: CMAN stations, buoys, ships and METAR data. We are also receiving Air Force Reconaissance data through LDM, but have yet to decode those data.

4. Perform feasibility testing of distributed object technology. Encapsulate the FORTRAN components of the legacy objective wind analysis algorithms in the C language on a remote analysis server (Solaris or HPUX workstation), and then have a prototype JAVA client and application server communicate with this server and the remote database server.

Documentation:

An Objective Analysis run consists of 4 steps equivalent to 4 major FORTRAN programs that run both on HP-UX 10.x and Sun Solaris 2.x platforms. In order to make each of these steps callable from any operating system/architecture on the Internet, they have to be distributed as objects. We accomplish this by wrapping (linking together and calling one program with another) the FORTRAN code in Java, an object oriented programming language. This development has, so far, been done exclusively on AOML machines. At the time that we were wrapping the FORTRAN code, only the Solaris 2.x platform had a version of the operating system that allowed the installation of the proper tools, mainly the latest version of the Java Development Kit. Therefore, after finding out that the version of HP-UX that AOML had available (HPUX 9) was not sufficient, we concentrated our efforts on prototyping distributed objects on Solaris.

Using Java Native Interface (JNI) and C, we were able to control the call (with and without parameters) to and return from of the FORTRAN programs to the main Java application. Then, by using JacORB, a freeware CORBA 2.0-compliant Object Request Broker (ORB), we created the interface that advertises the objects. To test these two crucial steps, we ran the all the Analysis steps with the client machine located in Taiwan and the analysis server located onsite at AOML (Miami, FL). Specifically, we ran a Java program located on a Sparc machine in Taiwan that invoked a request to the server in Miami. The server then executed the three main subprograms required to complete an analysis. Each subprogram is a separately wrapped unit of code. The analysis ran quite well and helped show us that a CORBA distribution scheme will indeed serve the project. CORBA allows applications to communicate with one another no matter where they are located or who has designed them. Using an ORB, the middleware that

establishes the client-server relationships between objects, a client can transparently invoke a method or function on a server object, which can be on the same machine or across a network. We are also investigating Java's Remote Method Invocation (RMI) technology for use in a heterogenous (Java client to Java server) distribution scheme.

In early June, the HRD owned machine designated as the Analysis server at NHC was upgraded to contain the requisite version of HPUX (10.20) and FORTRAN and C compilers that allowed us to replicate the AOML Solaris implementation of the Analysis subsystem on the HPUX platform in early July.

This task is on track to meet the projected September 1st deadline if it is not met ahead of schedule.

5. Begin initial design of product suite and development of routines for product delivery. These routines take the HRD Wind analysis results and deliver georeferenced images representing various fields such as wind swaths. Web access to these routines and GIS conformity among products is a priority. Investigate Interactive Data Language (IDL), Common Gateway Interface (CGI), and a generalized Java interface for dynamic product delivery.

Documentation:

Work on product generation routines will be completed in concert with the demand for new products. We have completed development on the subset of routines that represents the products that HRD had available in realtime in previous years. All the routines are now implemented in Research Systems' (RSI) Interactive Data Language (IDL). The routines are capable of plotting images to a local screen and/or generating images in a variety of file formats for delivery as hard copies. We are investigating different methods of delivering dynamically generated IDL products over the web. Both CGI and Java based methods are possible, but software licensing, product delivery speed and the intricacy of the code are still issues to be resolved for each proposed method.

We are currently experiencing problems with our prototype web cgi interface to IDL. These problems will be solved, but probably not in time to meet the projected September 1st deadline. The IDL procedures are, however, functional on their own when run outside of a web browser.

6. Complete evaluation of off-the-shelf relational, object-relational, and object-oriented database management systems. Procure and begin training for implementing and testing the chosen Database Management System with conventional atmospheric observations.

Documentation:

The fundamental tasks of designing, feeding, storing, extracting, and managing data in a database requires an analysis on the data requirements. A database is a data repository that provides a centralized and homogeneous view of data for multiple applications. HRD conducted a data analysis for the

Hurricane Wind Analysis System and designed a logical schema, a global view of the database. The system's schema is specified in terms of the semantic data modeling. A semantic data model is a mechanism for specifying the structure of the database and operations that can be performed on the data in the database. From our analysis, we concluded that a modern database management system was mandatory to serve Web applications to end-users. HRD conducted independent evaluations of available "off the shelf" relational, object-relational, and object-oriented commercial DBMSs including Oracle8, OpenBase, Mini SQL, NetCDF, OSMOS, and Informix Universal Server.

We have, furthermore, developed a database application prototype, the stormtrack database (http://storm.aoml.noaa.gov/Storms/index.html) and have elected to use an Oracle8 database server with object extensions to implement it. Oracle8 was chosen based on advantages in manageability, performance, scalability, transaction management and fault tolerance. We purchased Oracle8 Workgroup for WindowsNT (5-users) and database training units to train our application developers and database administrator on Oracle8.

Please refer to our Database Evaluation for further detail.

This milestone was met by its projected July 1st deadline.

Conferences and Papers

The project software developer and database specialist presented papers at the 14th International Conference on Interactive Information and Processing Systems (IIPS) for Meteorology, Oceanography, and Hydrology in Phoenix, AZ in January. The principal investigator lectured at the National Center for Atmospheric Research's (NCAR) Advanced Study Program Summer Colloquium. One day of the *Hurricanes at Landfall* Colloquium focused on Surface Winds and Storm Surge. An alpha version of the Java-based QCClient was used in laboratory exercises on hurricane surface wind fields (http://www.asp.ucar.edu/colloquium/1998/agenda.html). Developers also attended Sun Microsystems' JavaOne Conference (February, San Francisco) and the International Oracle User Group Conference (May in Orlando).

Picture of H*WIND's QCClient in use at the NCAR Colloquium.

Budget

The project is currently on budget. Matching funding from the National Institute for Building Science will arrive after AOML and ERL finance work out procedures. A potential long term issue is the number of concurrent database user licenses required for efficient use of the analysis system. We will explore this issue further by testing application performance under the current 5 user license.